## §§ 65.68-65.79

- (2) For process vents that become Group 1 process vents after a process change requiring a performance test to be conducted for the control device being used as specified in subpart G of this part, the owner or operator shall specify that the performance test has become necessary due to a process change. This specification shall be made in the notification to the Administrator of the intent to conduct a performance test as provided §65.164(b)(1).
- (3) Whenever a process change as described in §65.63(f) is made that changes the group status of a process vent from Group 1 to Group 2A, or from Group 1 to Group 2B, or from Group 2A to Group 2B, the owner or operator shall include a statement in the next periodic report after the process change that a process change has been made and the new group status of the process vents.
- (4) The owner or operator is not required to submit a report of a process change if one of the following conditions is met:
- (i) The change does not meet the definition of a process change in 65.63(f); or
- (ii) For a Group 2B process vent, the vent stream flow rate is recalculated according to §65.63(f) and the recalculated value is less than 0.011 standard cubic meter per minute (0.40 standard cubic foot per minute); or

- (iii) For a Group 2B process vent, the organic HAP or TOC concentration of the vent stream is recalculated according to §65.63(f), and the recalculated value is less than the applicable value in table 1 to this subpart; or
- (iv) For a Group 2B process vent, the TRE index value is recalculated according to §65.63(f) and the recalculated value is greater than 4.0.
- (c) Parameters for Group 2A without a recovery device. An owner or operator of a Group 2A process vent maintaining a TRE index value greater than 1.0 without using a recovery device shall report the information specified in the approved plan under §65.63(d).

## §§ 65.68-65.79 [Reserved]

TABLE 1 TO SUBPART D OF PART 65— CONCENTRATION FOR GROUP DETER-MINATION

Referencing subpart	Concentration 1
Subpart III of Part 60	NA.
Subpart NNN of Part 60	300 ppmv of TOC.
Subpart RRR of Part 60	300 ppmv of TOC.
Subpart G of Part 63	50 ppmv of HAP 2.

<sup>1</sup>The 50 ppm HAP concentration cutoff only applies to 40 CFR part 63, subpart G sources. Process vents subject to only 40 CFR part 60, subparts RRR or NNN are eligible for the 300 ppm TOC cutoff. There is no concentration cutoff for subpart III sources. The process vent provisions of subpart DDD are not consolidated under this subpart.

<sup>&</sup>lt;sup>2</sup> For process vents subject to subpart 6 of 40 CFR part 63, the owner or operator may measure HAP or TOC concentration with regard to the low concentration exemption provisions of this part.